




# DATA SHEET

**Filter media**  
Ultra-Web®

## Ultra-Web®

<b>Appearance</b>	Blue tinted, corrugated
<b>Use</b>	Pleatable filter media
<b>Composition</b>	Cellulose substrate with nanofiber layer
<b>Area weight</b>	114 g/m <sup>2</sup>
<b>Thickness</b>	0.28 mm
<b>Air Permeability (Frazier)</b>	520 m <sup>3</sup> /m <sup>2</sup> .h at 200 Pa
<b>ISO Classification</b> ISO 16890-2:2016(E) CERTIFICATE	ePM <sub>1</sub> 65% Test report number: 169-2
<b>Temperature (dry heat)</b>	
Continuous	65 °C
Peaks	80 °C
<b>Chemical resistance</b>	
Hydrolysis	N/A
Acids	Poor
Alkalis	Fair
Oxidising agents	Poor
Organic solvents	Fair
<b>Abrasion resistance</b>	Good
<b>Supports combustion</b>	Yes
<b>Application field</b>	Premium performance on ambient, extremely fine and non-fibrous dust and some abrasive dust. High filtration efficiency on very fine particulate of < 1 micron.  Typical applications include metallisation, laser cutting, pharmaceuticals, weld fume, shot blasting.

**Order online**   
shop.Donaldson.com

**Contact us**  
Donaldson.com

Publication 4218044GB • Rev. 12 • 0820  
Donaldson reserves the right to change or discontinue any model or specification at any time and without notice. Freedom from patent restrictions must not be assumed.